

ECOVOC SOLVENT CEMENT AND PRIVOC PRIMER

Rigid PVC Conduit, Duct and ENT Solvent Cement PVC and CPVC Primer – Low VOC

Why use Low VOC Solvent Cements and Primers?

Solvent Cement and Primer products contain hazardous chemicals and volatile organic compounds (VOC's), which emit smog-forming chemicals that can be harmful to users or installers and to our environment. Most of these products pollute indoor and outdoor air quality causing respiratory and eye irritation. Substituting with a Low VOC Solvent Cement and Primer reduces the VOC emissions and improves the air quality. Low VOC is defined as less than 510 g/L as per requirements for Leed's projects.

Ecovoc Solvent Cement: Premium Grade Clear

Ecovoc is a medium bodied solvent cement used for welding Rigid PVC Electrical Conduit, Duct and ENT pipe to Rigid Conduit fittings, creating a solid waterproof joint.

Important: Store cement between 5°C and 45°C. Stir before using. Ecovoc Solvent Cement has a VOC content of 475 g/L. If the cement is "jelly like", do not use and do not attempt to thin. For cold weather installations at temperatures below 5°C, the cement should be stored in a warm area to prevent thickening or gelation. Ecovoc solvent cement has a shelf life of 24 months if stored unopened at 22°C (72°F). Check the bottom of the can for the date of manufacture before using.

Privoc Primer: PVC and CPVC Primer (Clear)

Privoc Primer is used for priming PVC pipe and fittings prior to solvent welding.



Warnings and Dangers:

- Flammable
- Fumes Harmful
- Poison



Ecovoc Solvent Cement & Privoc Primer Can Sizes:

250ml, 475ml, 950ml and 4L



Benefits of using Low VOC Solvent Cement and Primer:

- Significantly lower emissions of smog-forming chemicals into the air from VOC's
- Better health and safety for individuals and installers using and/or handling these products
- Lower VOC emissions creates fewer fumes; reducing respiratory and eye irritation
- Low VOC Solvent Cement and Primer products are cost competitive
- Meets all industry certifications and standards

Certifications

Ecovoc Solvent Cement is certified to and manufactured to meet specifications defined in ASTM D2564.



D2564



C22.2
No. 211.1, 211.2

Our various pipe and fittings solutions have been manufactured to meet the need of our customers and their applications. Contact one of the Sales Centres for more information:

Sales & Distribution Centres:

Langley, BC, Canada
T/F 1.800.663.0696
F 1.800.663.6564

Woodbridge, ON, Canada
T/F 1.866.769.7473
F 905.856.3986

Laval, QC, Canada
T/F 1.800.465.9754
F 450.688.6624

Distribution Centres:

Calgary, AB, Canada
T/F 1.800.663.0696
F 1.800.663.6564

Winnipeg, MB, Canada
T/F 1.800.663.0696
F 1.800.663.6564



napcopipe.com