

PVC DWV SOLVENT WELD DRAIN, WASTE, VENT PIPE

Superior performance and lower lifecycle cost

PVC DWV Pipe and Fittings

The building construction industry has long embraced PVC as the preferred piping system over cast iron and copper for Drain, Waste and Vent plumbing systems. More and more contractors turn to PVC (Polyvinyl Chloride) pipe systems for residential, commercial and institutional projects. Easy to install, PVC pipe is approved for use in both combustible and non-combustible buildings.

Mechanical contractors and engineers are increasingly turning to NAPCO for rugged and durable PVC DWV solutions that deliver results on all counts:

- Efficiency
- Lower lifecycle cost
- Compliance with code requirements
- Longer product life
- Reduced environmental impact

Typical use for DWV pipe include:

- Removing sewage and gray water from a building
- Removing waste from fixtures in a residential application
- Roof venting which helps regulate air pressure in waste-system pipes and facilitates flow



PVC DWV

With a PVC DWV installation, contractors never have to worry about rusting, pitting, scaling or degradation, even when the system is exposed to moisture, salts and acids. Whatever the environment, interior and exterior walls remain smooth and deliver uninterrupted flow for many years. Since PVC is corrosion-proof, it requires less maintenance. PVC DWV/Sch 40 Dual-marked pipe is also lightweight and easier to handle, making installation faster and safer, especially when working in restricted or awkward spaces. There's no need for special equipment or additional manpower. Less expensive than conventional iron piping, our tough, impact-resistant PVC DWV can deliver years of uninterrupted service.

When you do the math, the bottom line is clear: PVC DWV is a smart investment choice for your current and long-term drain, waste and vent needs.

Pipe Availability

DWV/Sch 40 Dual-marked pipe is available in:

- Diameter: 1¼" to 12"
- Length: 10' and 20'

Why DWV Pipe

- Designed to last – PVC DWV delivers proven high-impact strength in colder temperatures.
- Cost-effective and efficient – Ease of handling and lighter weight means faster installations without the need for special equipment. Overall that translates into significant project cost savings.
- Choices to suit every need – PVC systems with several size options for pipe and fittings.
- Longer product lifecycle – PVC DWV is corrosion-proof it can easily outperform metal piping systems for longer periods of time.
- Impact resistant – The ruggedness of the PVC DWV system means less damage and waste on the job site.
- Safe handling – The solvent cementing application eliminates the need for specialized tools and the risks associated with torches.
- A system for all seasons – PVC DWV eliminates the need to work with other pipe materials at grade level because it can be used for both above and below grade.



D-Series

Fittings

We carry an extensive line of PVC DWV fittings, including bends, wyes, couplings, adapters, bushings and cleanouts. Our injection molded D Series fittings are available in sizes through 12" and are triple certified by CSA, NSF and UPC. Our fabricated fittings are available from 10" to 24" diameters. D Series fittings are intended for nonpressure applications.

Certification

PVC DWV/Sch 40 Dual-marked pipe is third party tested, CSA certified and NSF-14 certified to meet specifications defined in A STM D2665, D1785 and B137.3, as applicable.



Our various pipe and fittings solutions have been manufactured to meet the need of our customers and their applications. Contact one of the Sales Centres for more information:

Sales & Distribution Centres:

Langley, BC, Canada
T/F 1.800.663.0696
F 1.800.663.6564

Woodbridge, ON, Canada
T/F 1.866.769.7473
F 905.856.3986

Laval, QC, Canada
T/F 1.800.465.9754
F 450.688.6624

Distribution Centres:

Calgary, AB, Canada
T/F 1.800.663.0696
F 1.800.663.6564

Winnipeg, MB, Canada
T/F 1.800.663.0696
F 1.800.663.6564



1.855.624.7473 | napcopipe.com

NAPCO
2801 Post Oak Blvd., Suite 600
Houston, TX 77056