



TECHNICAL SPECIFICATION

NAPCO Gas Venting System GVS-65 (PVC) Concentric Vent Termination Kits

SCOPE

This specification covers the requirements for NAPCO GVS-65 (PVC) 2", 3" and 4" Concentric Vent Termination Kits. These kits are certified by Intertek Testing Services to ULC S636, Type IIA, for use as a vent termination with NAPCO GVS-65 pipe and fittings in installations with a flue gas temperature up to and including 65°C.

MATERIAL

GVS-65 Concentric Vent Termination Kits contain: Two lengths of SDR26 PVC pipe (trade sizes as shown below), One Cap and One Wye. Each kit also contains installation instructions for this product.

DIMENSIONS

Trade Size	Part Number	A (in)	B	C	D (Avg) (in)	L (in)
2" x 16"	52CVKGVS6502	17	3" SDR26 PVC Pipe	2" SDR26 PVC Pipe	3.5	33
2" x 28"	52CVKGVS6502-28	27				44
2" x 40"	52CVKGVS6502-40	39				56
3" x 20"	52CVKGVS6503	21	4" SDR26 PVC Pipe	2 ½" SDR26 PVC Pipe	4.5	39
3" x 32"	52CVKGVS6503-32	31				49
3" x 44"	52CVKGVS6503-44	43				61
4" x 36"	52CVKGVS6504	36	6" SDR26 PVC Pipe	4" SDR26 PVC Pipe	6.6	56

