



FABRICATED (APPEARANCE MAY VARY)

ASTM D2665, F1866, F2135, CSA B181.2 WHERE APPLICABLE

**1/32 BEND (11.25) SxH
PVC SOLVENT WELD DWV**

PART NO.	SIZE IN INCHES	L1	L2	S1	H1	T	W	D1
D1834	4	3	3/4	2 1/4	2 1/4	8 11/16	5 9/16	5 1/32
D1836	6	4 1/4	1	3 1/4	3 1/4	12 3/8	8	7 7/32
D1838	8	5 1/2	1 1/4	4 1/4	4 1/4	16 1/16	10 11/32	9 11/32
D18310	10	6 3/4	1 3/8	5 3/8	5 3/8	19 7/8	12 23/32	11 17/32
D18312	12	7 7/8	1 1/2	6 3/8	6 3/8	23 5/16	15	13 19/32

-- DIMENSIONS AND APPEARANCE ARE APPROXIMATE AND SUBJECT TO CHANGE
WITHOUT NOTICE DUE TO DESIGN OR PRODUCTION MODIFICATIONS
-- MOLDED FITTING TOLERANCE = ±1/8" OVERALL LENGTH
-- FABRICATED FITTING TOLERANCE = ±1" LINEAR, ± 2° ANGULAR

* MOLDED FITTING
† ASSEMBLED FROM MOLDED COMPONENTS
ALL OTHER FITTINGS ARE FABRICATED