

April 30, 2015

Re: SDR26 Gasketed Sewer Fittings Letter of Conformance

To Whom It May Concern:

H-Series Fittings 4" through 12" injection molded gasketed SDR 26 sewer fittings shall be manufactured in accordance with ASTM D3034, ASTM F1336 and CSA B182.2. They shall be injection molded from virgin PVC compound having a cell classification of 12454 or 13343 in accordance with, and certified by the National Sanitation Foundation (NSF), to meet ASTM D1784. Gaskets shall be manufactured in accordance with ASTM F477 or ASTM F913. Gaskets shall be firmly seated in fitting in order to ensure proper installation and to prevent dislocation or misalignment during system assembly. Gasket joints must comply with ASTM D3212 Internal Pressure Test (ex-filtration) at 10.8 psi and Vacuum Test (infiltration) of 22" mercury vacuum pressure at 5 degrees of gasket joint deflection. 4" through 8" molded SDR26 gasketed fittings exceed the standard and are certified at 200 psi.

Where available, reducing branches on injection molded 8", 10", and 12" tees, wyes, and tee-wyes shall be minimum SDR 18 wall thickness in the reducing branch body and reducing branch hub below the gasket race.

Our Gasketed SDR 26 Molded Sewer fittings are third party tested and listed by NSF and CSA to meet specifications defined in ASTM D3034 and CSA B182.2, where applicable.

Sincerely,



Jon Houghton

President